

## SAFETY DATA SHEET

# 5in1 Petrol fuel system treatment

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

#### Trade name

5in1 Petrol fuel system treatment

#### Product no.

687003

#### Unique formula identifier (UFI)

39NC-XY0W-M10V-3J8A

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

Additive

#### Use descriptors (REACH)

Product category	Description
	Additives to petrol or diesel fuel

#### ▼ Uses advised against

None known.

### 1.3. Details of the supplier of the safety data sheet

#### Company and address

##### **Maumo International BV**

P.O. Box 441

2990 AK Barendrecht

Nederland

+31 (0)180 699234

+31 (0)180 699235

www.maumo.nl

#### Contact person

Product Safety Department

#### E-mail

info@maumo.nl

#### Revision

19/09/2022

#### SDS Version

2.0

#### Date of previous version

09/09/2022 (1.0)

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Hazard pictogram(s)



### Signal word

Danger

### Hazard statement(s)

May be fatal if swallowed and enters airways. (H304)

Harmful to aquatic life with long lasting effects. (H412)

### Safety statement(s)

#### General

Keep out of reach of children. (P102)

#### Prevention

Avoid release to the environment. (P273)

#### Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)

Do NOT induce vomiting. (P331)

#### Storage

-

#### Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

### Hazardous substances

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C10, aromatics, > 1% naphthalene

### Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

### Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS No.: EC No.: 918-481-9 UK-REACH: Index No.:	95-100%	EUH066 Asp. Tox. 1, H304	
Polyolefin alkyl phenol alkyl amine	CAS No.: EC No.: UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Hydrocarbons, C10, aromatics, > 1% naphthalene	CAS No.: EC No.: 919-284-0 UK-REACH: Index No.:	1-3%	EUH066 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411	
Alkaryl polyether	CAS No.: EC No.: UK-REACH: Index No.:	1-3%	Aquatic Chronic 3, H412	
1,2,4-trimethylbenzene	CAS No.: 95-63-6 EC No.: 202-436-9 UK-REACH: Index No.: 601-043-00-3	<1%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
naphthalene	CAS No.: 91-20-3 EC No.: 202-049-5 UK-REACH: Index No.: 601-052-00-2	<1%	Flam. Sol. 2, H228 Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
mesitylene;1,3,5-trimethylbenzene	CAS No.: 108-67-8 EC No.: 203-604-4 UK-REACH: Index No.: 601-025-00-5	<1%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
2-ethylhexan-1-ol	CAS No.: 104-76-7 EC No.: 203-234-3 UK-REACH: Index No.:	<0.1%	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	[1]
propylbenzene;cumene	CAS No.: 98-82-8 EC No.: 202-704-5 UK-REACH: Index No.: 601-024-00-X	<0.05%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Carc. 2, H351 Aquatic Chronic 2, H411	[1]

-----

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[1] European occupational exposure limit.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

#### Burns

Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, Methaemoglobinaemia (naphthalene)

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

### 6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Recommended storage material

Keep only in original packaging.

#### Storage temperature

Dry, cool and well ventilated

Store out of direct sunlight.

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

—  
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Long term exposure limit (8 hours) (ppm): 184

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1200

—  
2-ethylhexan-1-ol

Long term exposure limit (8 hours) (ppm): 1

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 5,4

—  
propylbenzene;cumene

Long term exposure limit (8 hours) (ppm): 25

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 125

Short term exposure limit (15 minutes) (ppm): 50

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 250

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

1,2,4-trimethylbenzene

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	9512 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	16171 mg/kg bw/day
Long term – Local effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	15 mg/kg bw/day

2-ethylhexan-1-ol

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	11.4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	23 mg/kg bw/day
Long term – Local effects - General population	Inhalation	26.6 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	53.2 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	2.3 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	12.8 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	26.6 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	53.2 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	1.1 mg/kg bw/day

naphthalene

Duration	Route of exposure	DNEL
Long term – Systemic effects - Workers	Dermal	3,57 mg/kgbw/day
Long term – Systemic effects - Workers	Inhalation	25 mg/m <sup>3</sup>

propylbenzene;cumene

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	1.2 mg/kg bw/day

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Long term – Systemic effects - Workers	Dermal	15.4 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	16.6 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	250 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day

#### ▼ PNEC

##### 1,2,4-trimethylbenzene

Route of exposure	Duration of Exposure	PNEC
Freshwater		120 µg/L
Freshwater sediment		13.56 mg/kg
Intermittent release (freshwater)		120 µg/L
Marine water		120 µg/L
Marine water sediment		13.56 mg/kg
Sewage treatment plant		2.41 mg/L
Soil		2.34 mg/kg

##### 2-ethylhexan-1-ol

Route of exposure	Duration of Exposure	PNEC
Freshwater		17 µg/L
Freshwater sediment		284 µg/kg
Intermittent release (freshwater)		170 µg/L
Marine water		1.7 µg/L
Marine water sediment		28.4 µg/kg
Predators		55 mg/kg
Sewage treatment plant		10 mg/L
Soil		47 µg/kg

##### naphthalene

Route of exposure	Duration of Exposure	PNEC
Freshwater		0,0024 mg/L
Marine water		0,0024 mg/L

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

#### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

#### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

#### Individual protection measures, such as personal protective equipment

##### Generally

Use only UKCA marked protective equipment.

##### Respiratory Equipment

Type	Class	Colour	Standards
No special when used as intended.			

#### Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn.	-	-



#### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,38	> 240	EN374-2, EN374-3, EN388



#### Eye protection

Type	Standards
Safety glasses with side shields.	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Yellow

#### Odour / Odour threshold

Solvent

#### pH

No data available

#### Density (g/cm<sup>3</sup>)



0.8

Kinematic viscosity

7 mm<sup>2</sup>/s (40 °C)

Particle characteristics

Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)

No data available

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

>160

Vapour pressure

No data available

Relative vapour density

No data available

Decomposition temperature (°C)

No data available

Data on fire and explosion hazards

Flash point (°C)

>61

Ignition (°C)

No data available

Auto flammability (°C)

No data available

Lower and upper explosion limit (% v/v)

No data available

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Evaporation rate (n-butylacetate = 100)

No data available

Other physical and chemical parameters

No data available.

## SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

▼ 10.3. Possibility of hazardous reactions

None known.

▼ 10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method	OECD 403
Species	Rat
Route of exposure	Inhalation
Test	LC50 (4 hours)
Result	>5000 mg/m <sup>3</sup>
Other information	

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method	OECD 401
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>5000 mg/kg
Other information	

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method	OECD 402
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	>5000 mg/kg
Other information	

Product/substance	Polyolefin alkyl phenol alkyl amine
Test method	OECD 402
Species	Rat
Route of exposure	Dermal
Test	LD50
Result	>2000 mg/kg
Other information	

Product/substance	Polyolefin alkyl phenol alkyl amine
Test method	OECD 423
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>5000 mg/kg
Other information	

Product/substance	Hydrocarbons, C10, aromatics, > 1% naphthalene
Test method	OECD 403
Species	Rat
Route of exposure	Inhalation
Test	LC50 (dust)
Result	>4778 mg/m <sup>3</sup>

Other information

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene  
 Test method OECD 403  
 Species Rat  
 Route of exposure Inhalation  
 Test LC50  
 Result >4688 mg/m<sup>3</sup>  
 Other information

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene  
 Test method OECD 402  
 Species Rabbit  
 Route of exposure Dermal  
 Test LD50  
 Result >2000 mg/kg  
 Other information

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene  
 Test method OECD 401  
 Species Rat  
 Route of exposure Oral  
 Test LD50  
 Result 6318 mg/kg  
 Other information

Product/substance Alkaryl polyether  
 Test method  
 Species Rabbit  
 Route of exposure Dermal  
 Test LD50  
 Result >3000 mg/kg  
 Other information

Product/substance Alkaryl polyether  
 Test method OECD 423  
 Species Rat  
 Route of exposure Oral  
 Test LD50  
 Result >2000 mg/kg  
 Other information

Product/substance 1,2,4-trimethylbenzene  
 Test method  
 Species Rat  
 Route of exposure Inhalation  
 Test LC50  
 Result 10200 mg/m<sup>3</sup>  
 Other information

Product/substance 1,2,4-trimethylbenzene

Test method  
 Species Rat  
 Route of exposure Dermal  
 Test LD50  
 Result >3440 mg/kg  
 Other information

Product/substance naphthalene  
 Test method OECD 403  
 Species Rat  
 Route of exposure Inhalation  
 Test LC50  
 Result >0,4 mg/L  
 Other information

Product/substance naphthalene  
 Test method OECD 402  
 Species Rat  
 Route of exposure Dermal  
 Test LD50  
 Result >16000 mg/kg  
 Other information

Product/substance naphthalene  
 Test method OECD 401  
 Species Mouse  
 Route of exposure Oral  
 Test LD50  
 Result 533 mg/kg  
 Other information

Product/substance mesitylene;1,3,5-trimethylbenzene  
 Test method  
 Species Rat  
 Route of exposure  
 Test LC50  
 Result 10,2 mg/L  
 Other information

Product/substance mesitylene;1,3,5-trimethylbenzene  
 Test method  
 Species Rat  
 Route of exposure Dermal  
 Test LD50  
 Result >3440 mg/kg  
 Other information

Product/substance mesitylene;1,3,5-trimethylbenzene  
 Test method  
 Species Rat  
 Route of exposure Oral

Test	LD50
Result	>5000 mg/kg
Other information	

Product/substance	propylbenzene;cumene
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	>10000 mg/kg
Other information	

Product/substance	propylbenzene;cumene
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	2260 mg/kg
Other information	

#### Skin corrosion/irritation

Product/substance	Polyolefin alkyl phenol alkyl amine
Test method	OECD 404
Species	Rabbit
Duration	
Result	Adverse effect observed (Irritating)
Other information	

Product/substance	1,2,4-trimethylbenzene
Test method	
Species	Rabbit
Duration	
Result	Adverse effect observed (Irritating)
Other information	

Product/substance	mesitylene;1,3,5-trimethylbenzene
Test method	
Species	Rabbit
Duration	
Result	Adverse effect observed (Irritating)
Other information	

#### Serious eye damage/irritation

Product/substance	mesitylene;1,3,5-trimethylbenzene
Test method	OECD 405
Species	Rabbit
Duration	
Result	Adverse effect observed (Irritating)
Other information	

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Product/substance	naphthalene
Test method	
Species	Rat
Route of exposure	Inhalation
Target organ	
Duration	24 months
Test	NOAEL
Result	
Conclusion	Adverse effect observed
Other information	

Product/substance	propylbenzene;cumene
Test method	OECD 451
Species	Rat
Route of exposure	Inhalation
Target organ	
Duration	24 months
Test	
Result	
Conclusion	Adverse effect observed
Other information	

#### Reproductive toxicity

Product/substance	Polyolefin alkyl phenol alkyl amine
Test method	OECD 421
Species	Rat, female
Duration	
Test	
Result	
Conclusion	Adverse effect observed
Other information	

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### 11.2. Information on other hazards

##### ▼ Long term effects

None known.

##### ▼ Endocrine disrupting properties

None known.

#### Other information

naphthalene has been classified by IARC as a group 2B carcinogen.

propylbenzene;cumene has been classified by IARC as a group 2B carcinogen.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	48 hours
Test	EL0
Result	1000 mg/L
Other information	

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method	
Species	Fish, Oncorhynchus mykiss
Compartment	
Duration	96 hours
Test	LL0
Result	1000 mg/L
Other information	

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method	
Species	Algae, Pseudokirchneriella subcapitata
Compartment	
Duration	72 hours
Test	EL0
Result	1000 mg/L
Other information	

Product/substance	Polyolefin alkyl phenol alkyl amine
Test method	
Species	Algae
Compartment	
Duration	96 hours
Test	EC50
Result	5,4 mg/L
Other information	

Product/substance	Polyolefin alkyl phenol alkyl amine
Test method	
Species	Algae
Compartment	
Duration	96 hours
Test	NOEC
Result	3,65 mg/L
Other information	

Product/substance	Polyolefin alkyl phenol alkyl amine
Test method	

Species Daphnia, Daphnia magna  
 Compartment  
 Duration 21 days  
 Test NOEC  
 Result 3,38 mg/L  
 Other information

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene  
 Test method  
 Species Algae, Pseudokirchneriella subcapitata  
 Compartment  
 Duration 72 hours  
 Test EL50  
 Result >1 mg/L  
 Other information

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene  
 Test method  
 Species Daphnia, Daphnia magna  
 Compartment  
 Duration 48 hours  
 Test EL50  
 Result 1,4 mg/L  
 Other information

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene  
 Test method  
 Species Fish  
 Compartment  
 Duration 96 hours  
 Test LL50  
 Result 2-5 mg/L  
 Other information

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene  
 Test method  
 Species Algae, Pseudokirchneriella subcapitata  
 Compartment  
 Duration 72 hours  
 Test NOELR  
 Result 1 mg/L  
 Other information

Product/substance Hydrocarbons, C10, aromatics, > 1% naphthalene  
 Test method  
 Species Daphnia, Daphnia magna  
 Compartment  
 Duration 21 days  
 Test NOELR  
 Result 0,48 mg/L  
 Other information



---

Product/substance 1,2,4-trimethylbenzene  
 Test method  
 Species Daphnia, Daphnia magna  
 Compartment  
 Duration 48 hours  
 Test LC50  
 Result 3,6 mg/L  
 Other information

---

Product/substance 1,2,4-trimethylbenzene  
 Test method  
 Species Fish, Pimephales promelas  
 Compartment  
 Duration 96 hours  
 Test LC50  
 Result 7,72 mg/L  
 Other information

---

Product/substance naphthalene  
 Test method  
 Species Algae, Pseudokirchneriella subcapitata  
 Compartment  
 Duration 96 hours  
 Test EC50  
 Result 2,96 mg/L  
 Other information

---

Product/substance naphthalene  
 Test method  
 Species Daphnia, Daphnia magna  
 Compartment  
 Duration 48 hours  
 Test EC50  
 Result 2,16 mg/L  
 Other information

---

Product/substance naphthalene  
 Test method  
 Species Fish, Oncorhynchus gorboscha  
 Compartment  
 Duration 96 hours  
 Test LC50  
 Result 0,96 mg/L  
 Other information

---

Product/substance naphthalene  
 Test method  
 Species Daphnia, Daphnia pulex  
 Compartment  
 Duration 125 days  
 Test NOEC

---

Result 0,59 mg/L  
Other information

Product/substance naphthalene  
Test method  
Species Fish, *Oncorhynchus gorboscha*  
Compartment  
Duration 40 days  
Test NOEC  
Result 0,12 mg/L  
Other information

Product/substance mesitylene;1,3,5-trimethylbenzene  
Test method  
Species Algae, *Desmodesmus subspicatus*  
Compartment  
Duration 48 hours  
Test EL50  
Result 53 mg/L  
Other information

Product/substance mesitylene;1,3,5-trimethylbenzene  
Test method  
Species Daphnia, *Daphnia magna*  
Compartment  
Duration 48 hours  
Test LL50  
Result 6 mg/L  
Other information

Product/substance mesitylene;1,3,5-trimethylbenzene  
Test method  
Species Fish, *Carassius auratus*  
Compartment  
Duration 96 hours  
Test LL50  
Result 12,52 mg/L  
Other information

Product/substance mesitylene;1,3,5-trimethylbenzene  
Test method  
Species Algae, *Desmodesmus subspicatus*  
Compartment  
Duration 48 hours  
Test EL10  
Result 16 mg/L  
Other information

Product/substance mesitylene;1,3,5-trimethylbenzene  
Test method  
Species Daphnia, *Daphnia magna*

Compartment  
 Duration 21 days  
 Test NOEC  
 Result 0,4 mg/L  
 Other information

Product/substance propylbenzene;cumene  
 Test method  
 Species Algae, *Desmodesmus subspicatus*  
 Compartment  
 Duration 72 hours  
 Test EC50  
 Result 2,01 mg/L  
 Other information

Product/substance propylbenzene;cumene  
 Test method  
 Species *Daphnia*, *Daphnia magna*  
 Compartment  
 Duration 48 hours  
 Test EC50  
 Result 2,14 mg/L  
 Other information

Product/substance propylbenzene;cumene  
 Test method  
 Species Bacteria  
 Compartment  
 Duration 3 hours  
 Test EL50  
 Result >2000 mg/L  
 Other information

Product/substance propylbenzene;cumene  
 Test method  
 Species Algae, *Desmodesmus subspicatus*  
 Compartment  
 Duration 72 hours  
 Test EC10  
 Result 1,35 mg/L  
 Other information

Product/substance propylbenzene;cumene  
 Test method  
 Species *Daphnia*, *Daphnia magna*  
 Compartment  
 Duration 21 days  
 Test NOEC  
 Result 0,35 mg/L  
 Other information

---

Product/substance	propylbenzene;cumene
Test method	
Species	Fish, Danio rerio
Compartment	
Duration	28 days
Test	NOEC
Result	0,38 mg/L
Other information	

---

Product/substance	propylbenzene;cumene
Test method	
Species	Fish, Pimephales promelas
Compartment	
Duration	28 days
Test	NOEC
Result	0,38 mg/L
Other information	

## 12.2. Persistence and degradability

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Biodegradable	Yes
Test method	OECD 301 F
Result	>60%

---

Product/substance	Polyolefin alkyl phenol alkyl amine
Biodegradable	No
Test method	OECD 301 D
Result	4 % - Not readily - 28 days

---

Product/substance	naphthalene
Biodegradable	No
Test method	
Result	0 to 2 % - Not readily - 28 days

---

Product/substance	mesitylene;1,3,5-trimethylbenzene
Biodegradable	No
Test method	
Result	42% 28 days

---

Product/substance	propylbenzene;cumene
Biodegradable	No
Test method	
Result	70% 28 days

## 12.3. Bioaccumulative potential

Product/substance	Hydrocarbons, C10, aromatics, > 1% naphthalene
Test method	
Potential bioaccumulation	Yes

LogPow	2,8-6,5
BCF	99-5780
Other information	

Product/substance	1,2,4-trimethylbenzene
Test method	
Potential bioaccumulation	No data available.
LogPow	3,63
BCF	243
Other information	

Product/substance	naphthalene
Test method	
Potential bioaccumulation	No data available.
LogPow	36.5-168
BCF	3,4
Other information	

Product/substance	mesitylene;1,3,5-trimethylbenzene
Test method	
Potential bioaccumulation	No data available.
LogPow	3,42
BCF	161
Other information	

Product/substance	propylbenzene;cumene
Test method	
Potential bioaccumulation	No data available.
LogPow	3,55
BCF	35,48
Other information	

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### ▼ 12.6. Endocrine disrupting properties

None known.

#### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 14 – Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

**EWC code**

Not applicable.

**Specific labelling**

Not applicable.

**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

**SECTION 14: Transport information**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

**Additional information**

Not dangerous goods according to ADR, IATA and IMDG.

**14.6. Special precautions for user**

Not applicable.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Restrictions for application**

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

**Demands for specific education**

No specific requirements.

**SEVESO - Categories / dangerous substances**

Not applicable.

**Additional information**

Tactile warning.

**Sources**

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

**15.2. Chemical safety assessment**

No

**SECTION 16: Other information**

**Full text of H-phrases as mentioned in section 3**

EUH066, Repeated exposure may cause skin dryness or cracking.

H226, Flammable liquid and vapour.

H228, Flammable solid.  
H302, Harmful if swallowed.  
H304, May be fatal if swallowed and enters airways.  
H315, Causes skin irritation.  
H319, Causes serious eye irritation.  
H332, Harmful if inhaled.  
H335, May cause respiratory irritation.  
H336, May cause drowsiness or dizziness.  
H351, Suspected of causing cancer.  
H400, Very toxic to aquatic life.  
H410, Very toxic to aquatic life with long lasting effects.  
H411, Toxic to aquatic life with long lasting effects.  
H412, Harmful to aquatic life with long lasting effects.

[The full text of identified uses as mentioned in section 1](#)

= Additives to petrol or diesel fuel

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### [Additional information](#)

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

▼ The safety data sheet is validated by  
Maumo

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en